শেখ হাসিনার উদ্যোগ

বগুড়া পল্লী বিদ্যুৎ সমিতি-২

Bogura Palli Bidyut Samity-2

২য় বাইপাস, হেলেঞ্চাপাড়া, শাজাহানপুর, বগুড়া।

ISO 9001:2015 Certified

মুজিব শতবর্ষ

E-mail : bograpbs2@gmail.com, Web: pbs2.bogra.gov.bd

স্মারক নং-২৭.১২.১০৮৫.৫৭৪.০১.০৩৮.২৩. ১১৪০ তারিখঃ ১২ বৈশাখ ১৪৩০ বঙ্গাব্দ / ২৫ এপ্রিল ২০২৩ খ্রিঃ

বিষয়ঃ বগুড়া পবিস-২ এর প্রধান কার্যালয়ের প্রধান ফটকের গেট উচুঁ করণ কাজের কোটেশন প্রদানের পুনঃঅনুরোধজ্ঞাপনপত্র (RFQ)।

প্রতি,

বগুড়া পল্লী বিদ্যুৎ সমিতি-২ এর নিজস্ব তহবিলের আওতায় নিম্নোক্ত শর্ত ও বর্ণনানুযায়ী প্রধান কার্যালয়ের "প্রধান ফটকের গেট উচুঁ করণ" কাজের নিমিত্ত প্রকৃত পূর্ত নির্মাণ ঠিকাদারী প্রতিষ্ঠানের নিকট হইতে নিজস্ব লেটার হেড প্যাডে সীল মোহরকৃত খামে RFQ আহবান করা যাচ্ছে।

ক্র: নং	কাজের বিবরণ	একক	পরিমাণ	কার্য সম্পাদনের স্থান
1	**CE- 32.6.1.1** Dismantling of R.C.C. beam, lintel, column, drop wall, sun shade from any height and removal of debris to a safe distance. Col. 3×1'-3"×1'-8"×3'-0"= 18.79 cft	Cum	0.53	প্রধান কার্যালয়, বগুড়া পল্লী বিদ্যুৎ সমিতি-২ ২য় বাইপাস, হেলেঞ্চাপাড়া, শাজাহানপুর, বগুড়া।
2	**(A) CE-7.3** Reinforced cement concrete works with minimum cement content relates to mix ratio 1:1.5:3 having maximum water cement ratio = 0.40 and minimum fcr = 33.5 MPa, satisfying a specified compressive strength fc = 25 MPa at 28 days on standard cylinders as per standard practice of Code ACI/BNBC/ASTM, Cement conforming to BDS EN-197-1-CEM-I, 52.5N (52.5 MPa) / ASTM-C 150 Type - I, best quality Sylhet sand or coarse sand of equivalent F.M. 2.2 and 20 mm down well graded stone chips conforming to ASTM C-33 (Aggregate grading as per table shown in technical specification), conducting necessary tests, making and placing shutter in position and maintaining true to plumb, making shutter water-tight properly, placing reinforcement in position; mixing with standard mixer machine with hopper, fed by standard measuring boxes, casting in forms, compacting by vibrator machine and curing at least for 28 days, removing centering-shuttering after specified time approved; including cost of water, electricity, other charges etc. all complete, approved and accepted by the Engineer-in-charge. (Rate is excluding laboratory test fees, the cost of reinforcement and its fabrication, placing, binding etc. and the cost of shuttering & **CE-7.3.2** Pedestals, column, column capital, lift wall and RCC wall up to ground floor Col. 3×1'-3"×1'-8"×13'-0"= 81.41 cft	Cum	2.31	
	CE-7.3.3 Floor / roof slab, T-beam, L-beam and rectangular beam, tie beam, lintel, stair case slab and steps etc. upto ground floor Tee beam 2×20'-0"×1'-6"×1'-0"= 60.00 cft 2×3'-0"×1'-6"×1'-0"= 9.00 cft Slab 1×20'-0"×3'-0"×0'-5"= 25.20 cft 94.20 cft	cum	2.67	

ক্র: নং	কাজের বিবরণ	একক	পরিমাণ	কার্য সম্পাদনের স্থান
	CE-7.3.4 Cornice, railing, drop wall, louver, fins, sunshade, false ceiling, waffle and ribbed floor slab etc. up to ground floor 2×20'-0"×3'-0"×0'-4"= 39.60 cft 2×3'-0"×3'-0"×0'-4" = 5.94 cft 45.54 cft	cum	1.29	
2	**(B) CE-7.12** FORM WORK (Steel) : Centering and shuttering, including strutting, propping etc. (The formwork must be rigid enough both in and out of plane, to make the concrete surface true to the designed shape and size by using necessary MS sheets of minimum 16 BWG, angles of minimum size 40 mm x 40 mm x 5 mm, flat bars etc.) and removal of form for: 7.12.4 Pedestal, column, column capital, lift wall and wall up to ground floor 3×5'-10"×13'-0"= 227.37 sft	sqm	21.12	
	CE-7.12.6 T-beam, L-beam and rectangular beam etc up to ground floor 2×4'-0"×20'-0"= 160.00 sft 2×1'-0"×3'-0"= 6.00 sft 166.00 sft	sqm	15.42	
	CE-7.12.7 Floor and roof slab up to ground floor 1×20'-10"×3'-10"= 79.78 sft	sqm	7.41	
	CE-7.12.8 Cornice, railing, drop walls, louver, fins etc.: ground Floor 2×2×20'-0"×3'-0"= 240.00 sft 2×2×3'-0"×3'-0" = 36.00 sft = 276.00 sft	sqm	25.64	
3	**CE- 8.1** Supplying, fabrication and fixing to detail as per design ribbed or deformed bar reinforcement (excluding laboratory test fees) for Reinforced concrete, produced and marked in accordance with BDS ISO 6935-2:2016 (or standard subsequently released from BSTI) including straightening and cleaning rust, if any, bending and binding in position with supply of G.I. wires, conducting necessary laboratory tests etc. (excluding splices or laps) complete in all respect and accepted by the Engineer-in-charge (Measurement shall be recorded only on standard mass per unit length of bars, while dia of bars exceeds its **8.1.2** Grade 400 (B400DWR / B420DWR: complying BDS ISO 6935-2:2016/ASTM A615) ribbed or deformed bar produced and marked according to Bangladesh standard, with minimum yield strength, fy (ReH)= 400 MPa but fy not exceeding 480 MPa and whatever is the actual yield strength within allowable limit as per BNBC/ ACI 318, the ratio of ultimate tensile strength fu to yield strength fy, shall be at least 1.25 and minimum elongation after fracture and minimum total elongation at maximum force is 17% and 8% respectively up to ground floor Qnty B.F. Item No-2 Column 81.41 Cft @ 3.00 % =2.44 cft Tee beam 69.00 Cft @ 2.50 % =1.73 cft Slab 25.20 Cft @ 1.50 % =0.38 cft Raling 45.54 Cft @ 1.00 % = 0.46 cft = 5.01 cft @ 490.00 lbs/cft	kg	1113.47	

ক্র: নং	কাজের বিবরণ	একক	পরিমাণ	কার্য সম্পাদনের স্থান
4	**CE- 15.5** Minimum 6 mm thick cement sand (F.M. 1.2) plaster (1:4) with fresh cement to ceiling, R.C.C. columns, beams, surface of stair case, sunshades, cornices, railings, drop wall, louvers, fins and finishing the corners and edges including washing of sand, cleaning the surface, curing at least for 7 days, cost of water, electricity, scaffolding and other charges etc. all complete in all respect as per drawing and accepted by the Engineer-in-charge. (Cement: CEM-II/B-M) around floor. Qnty B.F. Item No-2 Column = 21.12 sqm Tee beam = 15.42 sqm Slab = 7.41 sqm Cornice = 25.64 sqm = 69.59 sqm	sqm	69.59	
5	**CE- 16.1.2** Exterior premium acrylic emulsion paint of approved best quality and color with high performance against dirt picking tendency and efflorosence resistence properties along with water resisting properties and resistance properties against fungi, fading and flaking from authorized local agent of the manufacturer in a sealed container; applying to exterior surface with surface preparation including cleaning drying, making free from dirt, grease, wax, removing all chalked and scaled materials, fungus, mending good the surface defects using sand paper and necessary scaffolding; applying necessary exterior sealer of specified brand on prepared surface; then applying necessary exterior putty of specified brand for levelling, spot filling, crack filling and cutting by sand paper/zero water paper; finally applying 2 coats of exterior emulsion paint spreading by brush/roller/spray & necessary scaffolding etc. upto desired finishing, elapsing specified time for drying or recoating; all complete in all floors and accepted by the Engineer-in-charge. Qnty B.F. Item No-4	sqm	69.59	

১. জেনারেল ম্যানেজার, বগুড়া পল্লী বিদ্যুৎ সমিতি-২ এর অনুকুলে সরকারি তহবিল বরাদ্দ করা হয়েছে এবং তিনি এর একটি অংশ যোগ্য পরিশোধের ক্ষেত্রে প্রয়োগ করতে ইচ্ছুক, যার জন্য এ কোটেশন দলিল জারি করা হয়েছে।

২. ইচ্ছুক সকল কোটেশনদাতা কর্তৃক পরিদর্শনের জন্য অভিপ্রেত পণ্য এবং সংশ্লিষ্ট সেবার বিস্তারিত বিনির্দেশ, ডিজাইন এবং নকশা দপ্তর চলাকালীন সময়ে সকল কার্যদিবসে বগুড়া পল্লী বিদ্যুৎ সমিতি-২ এর দপ্তরে প্রাপ্তিসাধ্য হবে।

৩. **'কোটেশন দলিল' ব্যবহার করে কোটেশন প্রস্তুত এবং জমা করতে হবে (কোটেশন দলিল বগুড়া পবিস-২ এর ওয়েব সাইট pbs2.bogra.gov.bd হতে সংগ্রহ করতে হবে)।**

৪. কোটেশন যথাযথভাবে প্রস্তুতপূর্বক ক্ষমতাপ্রাপ্ত স্বাক্ষরকারী কর্তৃক প্রতিটি পৃষ্ঠা স্বাক্ষর করে ৬ অনুচ্ছেদে উল্লিখিত তারিখ ও সময়ে বগুড়া পল্লী বিদ্যুৎ সমিতি-২ এর প্রধান কার্যালয় অথবা পবিস মনিটরিং ও ব্যবস্থাপনা পরিচালন (উঃ অঃ) পরিদপ্তর, বাপবিবো, ঢাকা এ রক্ষিত টেন্ডার বাক্সে জমা প্রদান করতে হবে।

৫. কোটেশন জমা এবং পণ্য সরবরাহে কোনো জামানত যেমন, কোটেশন জামানত এবং কার্য-সম্পাদন জামানতের (যদি চুক্তি সম্পাদিত হয়) প্রয়োজন হবে না।

৬. **সিলমোহরকৃত খামে ০২/০৫/২০২৩ খ্রিঃ তারিখ, রোজ মঙ্গলবার, বেলা ১১.৩০ ঘটিকায় কোটেশন বগুড়া পল্লী বিদ্যুৎ সমিতি-২ এর প্রধান কার্যালয় অথবা পবিস মনিটরিং ও ব্যবস্থাপনা পরিচালন (উঃ অঃ) পরিদপ্তর, বাপবিবো, ঢাকায় জমা প্রদান করতে হবে। কোটেশনের খামে "প্রধান ফটকের গেট উচুঁ করণ" কাজের জন্য কোটেশন এবং ০২/০৫/২০২৩ খ্রিঃ তারিখ, রোজ মঙ্গলবার, বেলা ১১.৩৫ ঘটিকার আগে খোলা যাবে না" লিখে অবশ্যই সুস্পষ্টভাবে চিহ্নিত করতে হবে। উল্লিখিত সময়ের পরে প্রাপ্ত কোটেশন গ্রহণযোগ্য হবে না।**

৭. প্রাপ্ত কোটেশনসমূহ উন্মুক্ত না করে মূল্যায়নের জন্য কোটেশন জমার সর্বশেষ সময়সীমা উত্তীর্ণের একই তারিখে মূল্যায়ন কমিটির কাছে পাঠাতে হবে।

৮. পাবলিক প্রকিউরমেন্ট বিধিমালা, ২০০৮ এর বিধি ৭১(৪) অনুসারে ক্রয়কারী কোটেশন আহবানের তারিখ হতে জমা প্রদানের জন্য প্রদত্ত সময় অনধিক ১০ (দশ) দিন এর নির্ধারিত সময়সীমা যথাসম্ভব কম বা যুক্তিসংগত করতে পারবেন।

৯. কোটেশন জমার নির্ধারিত সর্বশেষ তারিখ হতে ন্যুনতম ৯০ (নব্বই) দিন পর্যন্ত সকল কোটেশন বৈধ থাকবে।

১০. কোটেশন জমার সর্বশেষ সময়সীমা উত্তীর্ণের তারিখে প্রাপ্ত কোটেশন প্রকাশ্যে উন্মুক্ত করা হবে না।

১১. যদি চুক্তি সম্পাদন করা হয়, কোটেশনদাতার উদ্ধৃত দর বা মূল্যে মুনাফা ও ওভারহেড এবং সবধরণের কর, শুল্ক ও আবগারি, ফী, লেভি এবং আইনের অধীনে পরিশোধযোগ্য অন্যান্য চার্জ অন্তর্ভুক্ত থাকবে।

১২. দর টাকায় উদ্ধৃত করতে হবে এবং এ চুক্তির অধীন পরবর্তীতে মূল্য পরিশোধও টাকায় করা হবে। কোটেশনদাতার প্রস্তাবিত মূল্য, যদি গৃহীত হয়, তবে তা চুক্তিকালীন সময়ে স্থির অংকে থাকবে।

১৩. **কোটেশনদাতার চুক্তি করার আইনগত সক্ষমতা থাকতে হবে। কোটেশনদাতার যোগ্যতার প্রমাণস্বরূপ বৈধ ট্রেড লাইসেন্স, টিআইএন নম্বর ও ভ্যাট নিবন্ধন নম্বর এর সত্যায়িত অনুলিপি এবং কোনো তফসিলি ব্যাংক থেকে আর্থিক সচ্ছলতার সনদ দাখিল করতে হবে। এগুলো ব্যতীত কোটেশন অগ্রহণযোগ্য বলে বিবেচিত হতে পারে। কোটেশন দাতাকে মুসক ৬.৩ চালান সংযুক্তের সক্ষমতা থাকতে হবে।**

১৪. মূল্যায়ন কমিটি কোটেশনের সঙ্গে জমাকৃত তথ্য ও দলিলপত্রের ভিত্তিতে কোটেশন মূল্যায়ন করবে। চুক্তি সম্পাদনের জন্য সর্বনিম্ন মূল্যায়িত গ্রহণযোগ্য কোটেশন নির্ধারণের ক্ষেত্রে কমপক্ষে ৩(তিন)টি গ্রহণযোগ্য কোটেশনের প্রয়োজন হবে।

১৫. উদ্ধৃত একক দর এবং মূল্যের মধ্যে অসঙ্গতি থাকলে একক দর প্রাধান্য পাবে। কথায় এবং সংখ্যার মধ্যে অসঙ্গতির ক্ষেত্রে কথায় উদ্ধৃত দর/মূল্য প্রাধান্য পাবে। মূল্যায়ন কমিটি কর্তৃক নির্ণিত গাণিতিক সংশোধন গ্রহণে কোটেশনদাতা বাধ্য থাকবে।

১৬. কার্যাদেশ জারীর তারিখ থেকে ৩০ (ত্রিশ) দিনের মধ্যে নির্মাণ কাজ সম্পন্ন করতে হবে।

১৭. ক্রয় আদেশ যা সরবরাহকারী এবং ক্রয়কারীর মধ্যে অবশ্য পালনীয় চুক্তিতে বাধ্য করে তা অনুমোদনকারী কর্তৃপক্ষের অনুমোদন প্রাপ্তির ০৭ (সাত) কার্য দিবসের মধ্যে জারী করতে হবে।

১৮. ক্রয়কারী সকল কোটেশন বা ক্রয় কার্যক্রম বাতিল করার অধিকার সংরক্ষণ করে।

২৪/৪/২৩

(মোঃ আমজাদ হোসেন)
জেনারেল ম্যানেজার

অনুলিপিঃ (বিজ্ঞপ্তিটি নোটিশ বোর্ডে প্রচারের অনুরোধসহ)

১। পরিচালক, পবিস মনিটরিংও ব্য: প: (উঃঅঃ) পরিদপ্তর, বাপবিবো, ঢাকা
২। সিনিয়র সিস্টেম এনালিষ্ট, আইসিটি পরিদপ্তর, বাপবিবো, ঢাকা (বাপবিবোর্ডের ওয়েব সাইটে প্রকাশ করার অনুরোধসহ)।
৩। জেলা প্রশাসক, বগুড়া।
৪। পুলিশ সুপার, বগুড়া।
৫। সিনিয়র জেনারেল ম্যানেজার/জেনারেল ম্যানেজার, ---------------------------------পবিস-১/২/৩/৪।
৬। নিবাহী প্রকৌশলী, এলজিইডি/সড়ক ও জনপথ, বগুড়া।
৭। নির্বাহী প্রকৌশলী (এসওডি), বাপবিবো, বগুড়া।
৮। ডেপুটি জেনারেল ম্যানেজার-কারিগরী/গাবতলী/শেরপুর/সারিয়াকান্দি/ধুনট/সোনাতলা জোনাল অফিস, বগুড়া পবিস-২।
৯। সহ-জেনারেল ম্যানেজার-অর্থ/ওএন্ডএম/সদস্য সেবা/আইটি-১/২, বগুড়া পবিস-২।
১০। নোটিশ বোর্ড/ওয়েব সাইট **pbs2.bogra.gov.bd**, বগুড়া পবিস-২।

25.04.23

(মোছাঃ নুসরাত ইবরোজ)
এজিএম (প্রশাসন)